


# Benchtop Water Tester

## Benchtop CONDmeter

- ▲ SUPER LARGE LCD WITH MULTIPLE PARAMETERS DISPLAY
- ▲ POWERED BY ADAPTOR FOR CONTINUOUSLY USING
- ▲ DURABLE ELECTRODE HOLDER FOR LEFT & RIGHT SIDE PLACEMENT
- ▲ STABILITY INDICATION
- ▲ AUTO OR MANUAL TEMPERATURE COMPENSATION
- ▲ AUTO RANGING OR MANUAL RANGING
- ▲ UP TO 5 POINTS CALIBRATION POINTS
- ▲ DATA HOLD/MEMORY MAX/MEMORY MIN FUNCTION
- ▲ CALIBRATION & ELECTRODE INFORMATION REVIEW
- ▲ 99 POINTS MEMORIES W/ REAL TIME STAMP
- ▲ RS232 OUTPUT TO PC
- ▲ MEASURING PARAMETERS OF EACH MODEL:



86503



86553

### Optional:

4 PLUG UNIVERSAL ADAPTOR  
P/N:VB1099EX

### Standard Package:

Meter/ USA plug type adaptor/  
manual/probe/solution/ cable/  
software CD/probe stand

86503:COND.&TEMP.

86553:COND.&TEMP & PRINTER

	86503	86553
Cond. range	0~19.99, 0~199.9, 0~1999uS/cm; 0~19.99, 0~199.9mS/cm	0~19.99, 0~199.9, 0~1999uS/cm; 0~19.99, 0~199.9mS/cm
Cond. accuracy	+/-1% F.S +/- 1 digit	+/-1% F.S +/- 1 digit
Cond. resolution	0.05% of Full Scale	0.05% of Full Scale
Temp. Coefficient		0~10.0%/°C
Temp. range		0~80.0°C
Temp. accuracy		+/-0.5°C
Temp. resolution		0.1
Compliant probe		COND.
PRINTER	N/A	PRINTER
LCD size(mm)		40(H)x105(W)
Operating temp.&RH%		0~50°C, Humidity<80%
Storage temp.&RH%		-20~60°C, Humidity < 90%
Dimension(mm)		317(L)x168(W)x58(H)
Weight		150g
Power		9V adaptor