

## Table Top Low Speed Centrifuge **TL320**















TL320 is rugged Versatile and indispensable centrifuge for routine laboratories. As its offers wide variety of rotor and accessories can be used for preparation of samples in medical, industrial and research laboratories. It is high performance motor, **Maintenance free, Brushless** and **Microprocessor** controller for preselecting of speed and time.

- Easy entry of key pad
- Easy to read, digital display
- Display of correct speed & time volume
- Impulse key for short centrifuge
- Running time in minute, max 99 min
- Open lid key
- Lid locking
- Emergency lid lock release
- Motor over heating protection

- Max capacity: 32 x 15 ml / 8 x 50 ml
- Max speed: 5000 r/min
- Max ref: 4390 x g



MODEL	TL320							
Rotors	Swing 							
Cat No.	SB 4807						SB 0896	
Picture bucket								
Cat No.	M4/1	M8/2	M32/8	M24/6	M48/12			
Tube per rotor	4	8	32	24	48			
Capacity in ml	50ml		15 ml		7 ml			
ØXL in mm	29x115		16.5x120		13x75	13x100	15x62	8x96
Picture								
Max Speed	5000r/min	4000r/min	4000r/min				3000 r/min	
Max RCF	4390xg	2810 xg	2810xg				2120 xg	
Timer Range	0~99min							
Power Supply	AC220V50Hz10A							
Dimensions(LxWxH)	440x550x340mm							
Weight	45 kg							