

Table Top Low Speed Centrifuge **TL220**













TL220 is powerful versatile and indispensable centrifuge for routine laboratories. It is not only ideal for small laboratory; it can be also very useful in medium and large laboratories. It is high performance motor, **Maintenance free, Brushless** and **Microprocessor** controller for preselecting of speed and time.

- Easy entry of key pad
- Easy to read, digital display
- Display of correct speed & time volume
- Impulse key for short centrifuge
- Running time in minute, max 99 min
- Open lid key
- Lid locking
- Emergency lid lock release
- Motor over heating protection

- Max capacity: 24 x 10 ml
- Max speed: 4000 r/min
- Max ref: 2220 x g



MODEL	TL220					
Rotors	Angle 	Angle 	Angle 	Swing 		
Cat No.	AM 1810	AM 2410	AM 1220	SM 0815		
Picture bucket						
Cat NO.	P10		P20	M15		
Tube per rotor	18	24	12	8		
Capacity in ml	15 ml	10 ml	20ml	15 ml		
ØXL in mm	15x96	16x85	17x110	21x99	16.5x120	17.5x99
Picture tube						
Max Speed	4000r/min					
Max RCF	2220xg					
Timer Range	0~99min					
Power Supply	AC220V50Hz5A					
Dimensions(LxWxH)	330x420x275mm					
Weight	15kg					