

TES

1260 Humidity Temperature Meter

FEATURE:

- Dual LCD display.
- Dew Point Reading.
- Wet bulb Reading.
- MAX/MIN with Time Stamp.
- Data Hold function.
- °C / °F Switchable.
- DATA memory and read function.
(99 readings from LCD display)
- Auto Power Off.



SPECIFICATIONS

Measuring Range	Temperature : -20°C ~ 60°C (-4°F ~ 140°F) Humidity : 1%RH ~ 99%RH
Resolution	0.1°C /0.1°F /0.1%RH
Accuracy	Temperature : ±0.5°C, ±0.9°F Humidity : ±3%RH (at 25°C, 30 - 99% RH). ±5%RH (at 25°C, 1 - 30% RH).
Data Memory capacity	Manual recording : 99 data sets. (Direct reading from LCD display.)
Sampling Rate	2 times/sec
Operating Conditions	0°C ~ 60°C (32°F ~ 140°F) & below 99% R.H. (no condensation)
Power Source	9V Battery
Battery Life	Approx. 200 hours.
Size & Weight	193mm(L) × 59mm(W) × 26mm(H) / 140g
Accessories	Instruction manual, Battery, Carrying case.

TES

TES ELECTRICAL ELECTRONIC CORP.

7F, No. 31, Lane 513, Rui Guang Road, Neihu Dist. Taipei, Taiwan, R. O. C.

Tel : (02) 2799-3660

Fax : 886-2-2799-5099

E-Mail Address : tes@ms9.hinet.net

<http://www.tes.com.tw>