

TES-1362 Printing Humidity Temperature Meter

FEATURES

- Triple LCD Display for RH% Humidity, T1 for Air Temperature and T2 Type K Thermometer (-200 °C ~ 1333 °C).
- Dew Point Reading.
- Max / Min / Data Hold.
- Real Time Stamp.
- Periodically Print out from Pre-Set time Interval.



SPECIFICATION

Measuring Range	T1 : Temperature : - 20 °C ~ 60 °C (- 4 °F ~ 140 °F) Humidity : 10%RH ~ 95%RH T2 : Type K : - 200 ~ 1333 °C (- 58 ~ 2431 °F)
Resolution	0.1 °C /0.1 °F/0.1%RH
Accuracy	T1 : Temperature : +/- 0.8 °C , +/- 1.5 °F Humidity : +/- 3%RH (at 25 °C, 30...95%RH) T2 : Type K : - 50 °C ~ 500 °C , +/- (0.1%rdg + 0.8 °C) 500 °C ~ 1333 °C , +/- (0.2%rdg + 1.8 °C)
Input Protection	60V DC or 24 Vrms AC maximum input voltage on any Combination of input Connector.
Sampling Rate	1 time/sec
Operating Conditions	0 °C ~ 40 °C (32 °F ~ 104 °F) 10 ~ 80% R.H.
Power Source	6 pcs size AAA Alkaline Battery or 9V DC adaptor/500mA minimum.
Battery Life	Approx. 30 hours. (interval printing = 60 minute, not including beeper). 70 hours (except printing & beeper).
Size	193(L) x 74(W) x 37(H)mm
Weight	Approx. 385g
Accessories	1. Carrying case, Instruction manual, Battery, type K probe (TP-K01). 2. Two rolls thermo-paper. 3. Humidity / Temperature Probe.