

- BL620 : As experimentally general stirrer for the low viscosity materials, max. torque 29kg-cm(28Ncm), in the basis of water, stirring up to 20L and stirring speed range of 30-2000rpm
- BL610 : Experimental stirrer for the medium and low viscosity, range of stirrer is 40L for small volume of the medium viscosity, in the basis of water, and use widely from middle viscosity to low viscosity and max. torque is 5.8Kg-cm(57Ncm) and stirring speed range of 50-1000rpm

## Features

- 1 Sparkless, adapting durable and excellent brushless DC motor
- 2 Feedback control system maintains the accurate speed and uniform torque
- 3 No speed variation in the rating torque even though changing viscosity
- 4 Torque indicating lamp by changing viscosity
- 5 Electronic safety circuit
- 6 Speed display(Digital):
  - Digital Indicating function
  - Timer set-in function
  - Function of the positive/reverse rotation, automatic positive/reverse rotating direction set-in mode
  - Excellent stirring effect when using the automatic positive/reverse rotation set-in.
- 7 Smooth acceleration allows unit to reach set rpm without spillage
- 8 Narrow width designed for the effective application
- 9 Small, light weight and air-tight construction with less noise and designed in safety
- 10 Convenient, up and down control of the stirring shaft
- 11 Speed indicating(Scale) : Torque Indicating lamp
- 12 Protection function on the overloaded torque

## Specifications

Model	BL620	BL620D	BL610	BL610D
Stirring capacity (H2O)	20L		40L	
Viscosity (Max.)	10000mPas (low)		20000mPas (low, medium)	
Motor (output)	Brushless DC motor 60W		Brushless DC motor 60W	
Torque (Max.)	2.9kg-cm (28Ncm)		5.8kg-cm (57Ncm)	
Speed range	30-2000rpm		50-1000rpm	
Speed controller	Feedback control		Feedback control	
Speed display	scale	Digital	scale	Digital
Rotations	-	1. Right 2. Left(Operation) 3. Auto reverse (Reverse time setting)	-	1. Right 2. Left(Operation) 3. Auto reverse (Reverse time setting)
Timer	-	99hour 59min	-	99hour 59min
Chuck range	Ø1-10mm		Ø1-10mm	
Dimensions (W×D×H)	78×180×170mm		78×180×170mm	
Weight	2.8Kg		2.8Kg	
Electrical supply	220V 50/60Hz		220V 50/60Hz	
Price				
Price(Set)				