



- Space saving design with compact and light weight(MS12, MS15)
- Portable & ideal for stirring of the small vessels(MS12, MS15)
- Various sizes of the top plate
- Ceramic coated top plate
- Precise speed by electronic feedback control
- Max. speed : 1500rpm

Features

- ▶ Various sizes of the top plate and flexible choice
- ▶ Ceramic coated top plate provides excellent chemical resistance, thermal-proof, and corrosion resistance
- ▶ Reflective, bright white color ceramic coated plate enhances sample visibility
- ▶ Electronic feedback control maintains a precise speed
- ▶ Smooth acceleration of stirring speed ensures no spillage.

Specifications

Model		MS12	MS15	MS200	MS33
Type		Magnetic Stirrer			
Stirring	Speed	100~1500rpm			100~1300rpm
	Speed display	Scale(rpm)			
	Capacity(H ₂ O)	up to 1L	up to 2L	up to 5L	up to 15L
Speed Controller		Feedback control			
Top Plate		Ceramic coated top plate			
Dimensions	Plate area(mm)	120×120	150×150	180×180	300×300
	Overall(W×D×H)(mm)	160×280×107	160×280×107	200×310×107	310×430×120
Electrical Supply		220V 50/60Hz or 110V 50/60Hz			
Weight		2.4Kg	2.5Kg	3.4Kg	5.8Kg