

MICROLITRE CENTRIFUGE

— MIKRO 185

SMALL FOOTPRINT WITH UNMATCHED CAPACITY

The MIKRO 185 accommodates 12, 18 or 24 samples and is suitable for a wide range of tasks, thanks to a maximum RCF of 18,845 and a choice of four rotors. Spin column kits (minipreps) can also be used thanks to the special design of the 1213-A rotor.



— HIGHLIGHTS

- RPM: 200 - 14,000 min⁻¹
Adjustable up to 10,000 RPM in increments of 10, above in increments of 100
- max. RCF: 18,845
- max. capacity: 24 x 2.0 ml
- compact, high-performance microlitre centrifuge
- choice of 4 rotors
- IVD-conform according to directive 98/79/EC
- noise level of ≤ 54 dB (A) with rotor 1252-A
- impulse button for short centrifugation
- easy operation with keypad

— FEATURES





- plastic housing
- metal lid
- viewing port in the lid
- one-hand lid lock
- lid dropping protection
- emergency lid lock release
- light alloy chamber
- brushless drive
- error display
- imbalance monitoring and switch-off
- backlit panel with actual values of all parameters
- 3 adjustable messages after completion of the centrifugation run (audio + visual)

TECHNICAL DATA

MIKRO 185	
voltage *)	200 – 240 V 1 ~
frequency	50 – 60 Hz
consumption	330 VA
emission, immunity	EN/IEC 61326-1, class B
max. capacity	24 x 1.5 / 2.0 ml
max. RPM	14,000 min ⁻¹
max. RCF	18,845
running time	1 – 99 min: 59 s, ∞ continuous run, short cycle mode (impulse button)
dimensions (WxDxH)	261 x 353 x 228 mm
weight	approx. 11 kg
noise level	≤ 54 dB (A) with rotor 1252-A
Cat. No.	1203
100 – 127 V 1 ~ / 50–60 Hz	1203-01
emission, immunity	FCC class B

*) Other voltages on request.

AVAILABLE ROTORS

ANGLE ROTORS		angle	max. RPM	max. capacity	Cat. No.	page
	angle rotor, 24-place	45°	14,000 min ⁻¹	24 x 2 ml	1226-A	3
	angle rotor, 12-place	45°	14,000 min ⁻¹	12 x 2 ml	1252-A	3
	angle rotor, 18-place	45°	14,000 min ⁻¹	18 x 2 ml	1258-A	4
	angle rotor, 18-place for spin column kits	45°	14,000 min ⁻¹	18 x 2 ml	1213-A	4

— ANGLE ROTOR, 24-PLACE | 1226-A



Rotor

max. RPM max. RCF	14,000 min ⁻¹ 18,845
max. capacity	24 x 2 ml
run up run down, braked in sec	15 15
angle max. noise level	45° 59 dB (A)
Cat. No.	1226-A



Lid bioseal⁹⁾


Cat. No.	INCLUSIVE
-----------------	------------------



Vessels



capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0	0.5
Ø x L in mm	6 x 18	6 x 45	8 x 30	8 x 45	11 x 38	11 x 38	10.7 x 36
max. RCF ²⁾	18,845	18,845	18,845	18,845	18,845	18,845	17,749
radius in mm	86	86	86	86	86	86	81
Cat. No.	microliter tubes						Pediatric



Adapter

boring Ø x L in mm	6 x 40	6 x 40	8 x 40	8 x 40	-	11.2 x 39	11.2 x 39
vessels per rotor	24	24	24	24	24	24	24
Cat. No.	2024	2024	2023	2023	2031⁷⁾	-	0788

— ANGLE ROTOR, 12-PLACE | 1252-A



Rotor

max. RPM max. RCF	14,000 min ⁻¹ 15,558
max. capacity	12 x 2 ml
run up run down, braked in sec	15 15
angle max. noise level	45° 54 dB (A)
Cat. No.	1252-A



Lid

Cat. No.	INCLUSIVE
-----------------	------------------



Vessels



capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0	0.5
Ø x L in mm	6 x 18	6 x 45	8 x 30	8 x 45	11 x 38	11 x 38	10.7 x 36
max. RCF ²⁾	15,558	15,558	15,558	15,558	15,558	15,558	14,462
radius in mm	71	71	71	71	71	71	66
Cat. No.	microliter tubes						Pediatric




Adapter

boring Ø x L in mm	6 x 40	6 x 40	8 x 40	8 x 40	-	11.2 x 39	11.2 x 39
vessels per rotor	12	12	12	12	12	12	12
Cat. No.	2024	2024	2023	2023	2031⁷⁾	-	0788

2) Please note that the RCF values indicated refer only to rotor performance. The max. permissible RCF of tubes used should be verified with the individual manufacturers. The max. RCF for glass tubes annotated with footnote 2) is 4,000.
 5) Tested by the TÜV in conformity with DIN EN 61010, section 2 - 020.
 7) For centrifugation at high speeds, we recommend to use conical, phenol-resistant adapters 2031.

— ANGLE ROTOR, 18-PLACE | 1258-A



Rotor

max. RPM max. RCF	14,000 min ⁻¹ 16,654
max. capacity	18 x 2 ml
run up run down, braked in sec	15 15
angle max. noise level	45° 56 dB (A)
Cat. No.	1258-A

Lid

Cat. No.	INCLUSIVE
-----------------	------------------




Vessels



capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0	0.5
Ø x L in mm	6 x 18	6 x 45	8 x 30	8 x 45	11 x 38	11 x 38	10.7 x 36
max. RCF ²⁾	16,654	16,654	16,654	16,654	16,654	16,654	15,558
radius in mm	76	76	76	76	76	76	71
Cat. No.	microliter tubes						Pediatric



Adapter



boring Ø x L in mm	6 x 40	6 x 40	8 x 40	8 x 40	-	10.2 x 19	11.2 x 39
vessels per rotor	18	18	18	18	18	18	9
Cat. No.	2024	2024	2023	2023	2031⁷⁾	-	0788

— ANGLE ROTOR, 18-PLACE | 1213-A



Rotor


max. RPM max. RCF	14,000 min ⁻¹ 16,654
max. capacity	18 x 2 ml
run up run down, braked in sec	16 15
angle max. noise level	45° 57 dB (A)
Cat. No.	1213-A

Lid bioseal⁹⁾

Cat. No.	INCLUSIVE
-----------------	------------------




Vessels



capacity in ml	0.2	0.4	0.5	0.8	1.5	2.0	1.5	2.0
Ø x L in mm	6 x 18	6 x 45	8 x 30	8 x 45	11 x 38	11 x 38	11 x 38	11 x 38
max. RCF ²⁾	16,654	16,654	16,654	16,654	16,654	16,654	16,654	16,654
radius in mm	76	76	76	76	76	76	76	76
Cat. No.	microliter tubes						micro spin columns	



Adapter



boring Ø x L in mm	6 x 40	6 x 40	8 x 40	8 x 40	10.2 x 19.3	11.2 x 39	10.2 x 19.3	11.2 x 39
vessels per rotor	18	18	18	18	18	18	18	18
Cat. No.	2024	2024	2023	2023	2031⁷⁾	-	2031⁷⁾	-

2) Please note that the RCF values indicated refer only to rotor performance. The max. permissible RCF of tubes used should be verified with the individual manufacturers. The max. RCF for glass tubes annotated with footnote 2) is 4,000.
 5) Tested by the TÜV in conformity with DIN EN 61010, section 2 - 020.
 7) For centrifugation at high speeds, we recommend to use conical, phenol-resistant adapters 2031.

CERTIFICATIONS / REGISTRATIONS

Product certification:



Product registration:



Company certifications:



DOWNLOADS

[↓ Operating Manual – MIKRO 185](#)

[↓ General Catalog](#)

DIMENSIONS

