

TL200&TL220 are powerful versatile and indispensable centrifuge for routine laboratories. It is not only ideal for small laboratory; it can be also very useful in medium and large laboratories. It is high performance motor, **Maintenance free**, **Brushless** and **Microprocessor** for preselecting of speed and time.

- Easy entry of key pad
- Easy to read, digital display
- Display of correct speed & time volume
- Impulse key for short centrifuge
- Running time in minute, max 99 min
- Open lid key
- Lid locking
  
- Motor over heating protection



MODEL	TL220			TL200		
Max Speed	4000r/min			4000r/min		
Max RCF	2220xg			1700xg		
Timer Range	0~99min			0~99min		
Power Supply	AC220V50Hz5A			AC220V50Hz5A		
Dimensions(LxWxH)	330x420x275mm			230x310x240mm		
Weight	15kg			10kg		
	Volume	Max Speed(r/min)	MaxRCF( xg)	Volume	Max Speed (r/min)	Max RCF( xg)
Angle	18x15ml	4000	2220	8x20ml	4000	1700
Angle	24x10ml	4000	2220	12x10ml	4000	1700
Angle	12x20ml	4000	2220	12x15ml	4000	1700
Swing	8x15ml	4000	2220			

MODEL	TL320		TL300	
Max Speed	5000r/min		5000r/min	
Max RCF	4390xg		2760xg	
Timer Range	0~99min		0~99min	
Power Supply	AC220V50Hz10A		AC220V50Hz10A	
Dimensions(LxWxH)	440x550x340mm		410x490x310mm	
Weight	45 kg		30kg	
	Max Speed (r/min)	MaxRCF( xg)	Max Speed(r/min)	MaxRCF( xg)
48x7ml	4000	2810	----	----
72x7ml	4000	2810	----	----
32x15ml/24x15ml	4000	2810	4200	2760
4x50ml	5000	4390	4200	2760
8x50ml	4000	2810	----	----
4x100ml	4000	2810	----	----
16x15ml	4000	2810	4200	2760