

# **USB TEMPERATURE DATALOGGER**

## **NEW + PATENTED**



### Features

- USB datalogger shape with NEW DESIGN patent
- Smart logger with tripod receptacle and wrist strip for long time recording and hang on the wall
- Recording anywhere, anytime and date
- LCD display and bright red and green LEDs for visible and recognize it is still logging or exceed HI/LO threshold.
- There are two models for temperature logger, either with LCD display or without LCD display.
- Press button to activate logging start (set up first), long press button to inactivate logging.
- Water resistant and vented design for accurate sensing
- Smart and modern sensor cap design prevents dirt and protect sensor.
- Logger without cradle, easy to set up and upload, saving cost and convenient.
- Easy to replace battery compartment

#### Standard accessories

 Meter. Battery. Manual. Wrist strip. CD software .USB cap and blue sensor cap

### **Application**

- Unattended Temperature monitoring and recording,
- Process monitoring for maintenance and troubleshooting applications
- Environmental monitoring in storage warehouse, recording during transportation or food in process

## **Specifications**

TO. //\_ //

| Spec./ Model no.              | 98580  | 98581                   |
|-------------------------------|--|-------------------------|
| Record data                   | Temperature  |                         |
| LCD display                   | YES ( 985805 No display)                                       | YES ( 985815 No display |
| LED (Red , Green)             | YES  |                         |
| Sample interval               | From 1 second to 6 hours ( Sec.:0~59 , Min.: 0~59 , Hour: 0~5) |                         |
| Hi/Lo threshold setting       | YES  |                         |
| Hanging wrist                 | YES  |                         |
| Logger mode                   | Key start/stop , Immdiately, Schedule , Real-time              |                         |
| Temp.range                    | -40.0~85.0°C (-40~185°F)                                       |                         |
| Accuracy                      | +/-0.6°ℂ (-20~50°ℂ ),others+/-1.2°ℂ                            |                         |
| Memory capacity- Total ( or ) | 16000  | 32000                   |
| Power                         | 3.6 Lithium battery  |                         |
| Opeating Temp.                | <b>0~5</b> 0°ℂ (32~122°F)                                      |                         |
| Operating RH                  | ,<80%  |                         |
| Logger size                   | 135.7 x 28.5 (with cap ) mm                                    |                         |