

# Thermomac

## Heating Mantle

### HM SERIES



The device is widely used for heating in the school laboratory, industrial and mining , food processing, biochemistry, agriculture, petrochemicals engineering and pharmaceuticals industry for the liquid.

### Characteristics:



- Controlled up to 450°C
- The entire range is manufactured from powder-coated steel.
- Electronic temperature regulation mode with characteristics of stepless speed adjustable, uniform temperature, heating fast, and safety.
- Featured by anti-corrosion, age-resistant, durable and safe.
- Range of sizes available
- Integrated clamp fitting
- CE marked
- 2 years warranty



## Technical Specification:

Model	Flask capacity	Exterior Size(mm)	Packaging Size(mm)	Voltage(V)	Max. Use Temp	Power(W)
HM50	50ml	200×200×160	230×230×170	220V, 50Hz	450°C	80
HM100	100ml	200×200×160	230×230×170	220V, 50Hz	450°C	100
HM250	250ml	200×200×160	230×230×170	220V, 50Hz	450°C	150
HM500	500ml	200×200×160	230×230×170	220V, 50Hz	450°C	250
HM1000	1000ml	260×260×200	290×290×220	220V, 50Hz	450°C	350
HM2000	2000ml	300×300×230	330×330×250	220V, 50Hz	450°C	450
HM4000	4000ml	310×310×250	330×330×270	220V, 50Hz	450°C	700
HM6000	6000ml	350×350×270	380×380×290	220V, 50Hz	450°C	900
HM10000	10000ml	420×420×320	450×450×340	220V, 50Hz	450°C	1200

## Ordering Information:

PART CODE	DESCRIPTION
001-001-001	HM50 Heating mantle 50ml capacity
001-001-002	HM100 Heating mantle 100ml capacity
001-001-003	HM250 Heating mantle 250ml capacity
001-001-004	HM500 Heating mantle 500ml capacity
001-001-005	HM1000 Heating mantle 1000ml capacity
001-001-006	HM2000 Heating mantle 2000ml capacity
001-001-007	HM4000 Heating mantle 4000ml capacity
001-001-008	HM6000 Heating mantle 6000ml capacity
001-001-009	HM10000 Heating mantle 10000ml capacity