

# SHAKING INCUBATOR

The optimum performance **SHAKING INCUBATOR** with its proven features & stylish design

## FTSH series models



### FEATURE

- Brushless AC motor
- Safety device.
- Universal spring rack (option)
- Shaking orbital motion
- Digital PID controller

### GENERAL SPECIFICATIONS

Temp Controller	Digital PID controller
Temp Range FTSH Type	Amb +5 °C to 60 °C
Temp Range FTSH-L Type	15 °C-60 °C
Speed Range	10-350 rpm
Display	LED display
Drive System	Belt type
Motor	AC motor
Circulation Fan	3.5" convection fan x 2 EA
Lid	Acrylic blue
Safety Device	Over temp. Protector, Door detector
Standard Plate	250 mL (flask) x 16 EA

### OPTIONAL ACCESSORY



Plate of flask



Spring rack

### OPTIONAL ACCESSORY

(MODELS) FLASK	FTSH- 501/501L	FTSH- 121/121L	FTSH- 220/220L	FTSH- 301(Mini)
100 mL	25 EA	36 EA	60 EA	12 EA
250 mL	16 EA	25 EA	40 EA	9 EA
500 mL	9 EA	16 EA	24 EA	5 EA
1000 mL	4 EA	9 EA	15 EA	4 EA
Spring Rack (mm)	387 x 375	480 x 430	720 x 600	280 x 280
Plate (mm)	385 x 375	480 x 430	720 x 600	280 x 280



### INDIVIDUAL SPECIFICATIONS PER MODEL

MODELS	FTSH-501/501L	FTSH-121/121L	FTSH-220/220L	FTSH-301 (Mini)
Internal Dimension (L x D x H) (mm)	510 x 430 x 380	550 x 500 x 450	790 x 650 x 450	280 x 280
External Dimension (L x D x H) (mm)	520 x 700 x 520	780 x 680 x 910	1,020 x 820 x 910	320 x 320 x 300