


## USB HAND HELD THERMO-HYGROMETER

**NEW**



RH calibration solution  
33% - 99033S (Green)  
75% - 99075S (Blue)



### Features

- Compact size with structure NEW UTILITY patent
- Measure Temperature and Relative humidity, model 98873 monitor Wet bulb global temperature and Heat index for heat stroke prevention
- Self-calibration by salt bottle with 33% low humidity and 75% high humidity solution. Salt bottles and
- USB software with CD are optional package
- Hold function for holding readings on display
- Large dual display with battery low indication
- Quick response. High accuracy
- Big LCD display with high resolution
- Enable Auto power off and disable function
- Warranty in 2 years from purchasing

### Standard Accessories

- Meter, Battery, Operation manual and carrying case

### Applications

- HVAC & Home inspection for examining the heating and air conditioning systems.
- Construction & Industrial inspection
- Outdoors weather monitoring avoid unnecessary heat stroke while training outside



### Specifications

	98871	98873	98875
Temp.range		-20~50C (-4~122F)	
Accuracy		+/-0.6C	
RH % range		0.1~99.9%	
Accuracy		+/-3% (10-90%), others +/-5%	
Heat Index (HI)	N/A	N/A	YES
Wet Bulb Global Temp.(WBGT)	N/A	N/A	YES
Dew Point Temp.(DP)	N/A	YES	YES
Wet Bulb Temp. (WB)	N/A	YES	YES
HI/LO alarm	N/A	YES	YES
Self-calibration	N/A	YES	YES
Maximum/ Minimum/Recall		YES	
Reset		YES	
Memory	N/A	99 point	64000 point
Average		YES	
Power		AAA x 3 pcs	
USB Interface	N/A	NO	YES
Operating Temp.RH		0~50C(32~122°F) , <80%RH	
Meter size		160*60*40mm (Meter) , Sensor tip( 31mm)	