



# DM0636 Multi-Purpose Low-speed Centrifuge

- Speed from 300-6000 rpm
- Maximum capacity : 100 mLx4
- 9 Acceleration/10 Brake speed settings to ensure optimal separation
- A wide range of rotors optional(fixed angle and swing-out rotors)
- Automatic rotor identification
- Pulse Key for quick spin
- 9 procedures stored in memory makes the operation much simplified
- Maintenance-free brushless DC motor
- Suitable for tubes with caps, blood collection or urine tubes
- Comprehensive and versatile range of accessories

Model : DM0636

[Product Comparison](#)

[View Accessories](#)

[Product Consulting](#)

## PRODUCT PARAMETERS

Cat.No.	9115001123
Speed Range	300-6000rpm increment:10rpm
Max. RCF	4100xg
Speed Accuracy	±20rpm
Rotor type	-
Rotor Capacity	100mLx4
Run Time	30sec-99mins/continuous
Display	LCD
Safety Devices	Door Imbalance protection Over speed & Over temperature detection
Acceleration/Braking time[Sec]	9↑/10↓steps
Program	-
Preloaded Program	-
Program Memory	9
Motor	Brushless DC motor
Power	660W; Single-phase AC220V-240V, 50Hz/60Hz, 6.3A; AC110V- 120V,50Hz/60Hz,10A

Dimension[WxDxH]	570×445×295mm
Weight	36kg
Noise	≤65dB
Advanced features	speed/rcf switch; Rotor identification

## DM0636 Multi-Purpose Low-Speed Centrifuge



DLAB SCIENTIFIC CO.,LTD.

No.31, Yu'an Road, Beijing Airport Economic Core Zone, Shunyi District,Beijing101318,China

Tel: 86-10-85653451/52/53,60498800

Fax: 86-10-85653383

E-mail: [info@dlabsci.com](mailto:info@dlabsci.com)

Service: [service@dlabsci.com](mailto:service@dlabsci.com)

Service Hotline: 400-1100-556

Web: [www.dlabsci.com](http://www.dlabsci.com)