

MG214Ai

A Top Quality series of Analytical Balances that combine elegance with highly reliable measuring performance. All MG models are equipped with a large graphic display for easy reading and user friendly operations with many functions with a double case structure for high durability and ergonomic keypad.

MG balances have an extensive recipe database, GLP and many embedded advanced features that make them perfect for use in laboratory, research departments, compounds formulation and quality control applications.

Overview

Electromagnetic force restoration weighing system

External or automatic internal calibration

Recipe database: 99 recipes can be stored, each with up to 20 ingredients

Large Graphic display allows efficient and easy operations

Multilanguage: EN-DE-FR-IT-ES-PT

GLP/ISO record keeping of weight values with date, time and serial number

Large glass draught shield with 3 sliding doors for easy access to the items being weighed

Plastic protection cover

Response time (sec.)

Repeatibility

Technical Features

Capacity [Max] 220g (https://www.belengineering.com/01_capacity/220g/)

Resolution [d] 0,1mg (https://www.belengineering.com/02_resolution/0-1mg/)

 Calibration
 Automatic internal (https://www.belengineering.com/03_calibration/automatic-internal/)

≤4 (https://www.belengineering.com/08_responsetime/%e2%89%a44/)

0,1mg (https://www.belengineering.com/06_repeatibility/01mg/)

Pan size Ø 80 mm (https://www.belengineering.com/04_pan-size/o-80-mm/)

Linearity ± 0,0003g (https://www.belengineering.com/07_linearity/%c2%b1-00003g/)

Verification [M]

Minimum Load 10 mg

Display GRAPHIC

Tare Range (Subtractive) 220 g

Span Drift In +10...+30°c $\pm 2 \text{ ppm/°C}$

Interface RS232

Database Capacity 99

Windshield Type And Dimensions 3 sliding windows / 162x171x225 mm

Working Temperature 5 - 35°C (15-30°C for verified models)

Power Supply 110-230Vac. 50/60Hz, output 24V 500mA 13VA

Power Consumption (Max) 2 Watt

Calibrates With (Class) 200 g (E2)

Balance Dimensions (W X L X H) 215 x 345 x 345 mm

Net Weight / Gross Weight, Approx. 6,6 / 9,2 Kg

Package Size (W X L X H) 390 x 520 x 630 mm